


LAMP PHOTOMETRIC REPORT

MODEL: 93DFLD6040/BL		
POWER: 60W	VOLTAGE: 230V	WORKING VOLTAGE: 230V
MANUFACTURER: Elmark Industries JSC		

TOTAL FLUX: 6023.4 lm



γ	C0	C45	C90	C135	C180	C225	C270	C315	γ	Φ zone	Φ total	%
10	5539	6371	6910	5973	5480	6088	6956	6475	0- 10	619.0	619.0	10.3
20	3846	5039	6305	4754	3927	4864	6429	5193	10- 20	1584	2203	36.6
30	2208	3617	4136	3442	2347	3574	4322	3811	20- 30	1972	4175	69.3
40	234.4	1449	1397	1229	267.8	1391	1522	1664	30- 40	1353	5528	91.8
50	60.53	174.4	278.3	149.5	64.05	149.6	296.0	184.2	40- 50	396.9	5925	98.4
60	19.90	28.00	57.11	25.34	20.51	27.22	59.96	30.60	50- 60	78.40	6003	99.7
70	3.992	5.847	8.115	4.966	4.811	5.233	8.932	6.237	60- 70	17.92	6021	100
80	0.2805	0.4085	0.4883	0.3939	0.3262	0.3502	0.4015	0.3476	70- 80	1.929	6023	100
90	0.2129	0.2510	0.3358	0.2694	0.3262	0.3663	0.4259	0.3555	80- 90	0.3540	6023	100
100									90-100			
110									100-110			
120									110-120			
130									120-130			
140									130-140			
150									140-150			
160									150-160			
170									160-170			
180									170-180			
DEG	LUMINOUS INTENSITY:cd									UNIT:lm		

C Range: 0 - 360DEG
 C Interval: 10.0DEG
 Test Speed: HIGH
 Temperature: 25.3°C
 Operators:
 Test Date: 31 August 2022

γ Range: 0 - 90DEG
 γ Interval: 2.5DEG
 Test System: EVERFINE GO-2000A_V1 SYSTEM V2.00.456
 Humidity: 65.0%
 Test Distance: 6.265m [K=1.0000]
 Remarks:

```

γ Range: 0 - 90DEG
γ Interval: 2.5DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.00.456
Humidity:65.0%
Test Distance:6.265m [K=1.0000]
Remarks:

```

```

γ Range: 0 - 90DEG
γ Interval: 2.5DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.00.456
Humidity:65.0%
Test Distance:6.265m [K=1.0000]
Remarks:

```