

EL[®]MARK

The Brand of Electricity

MOVEBLE LED SPOTLIGHTS

DLTS SERIES DRIVER

GENERAL INFORMATION »

- ∴ Rated voltage: 220-240V/ 50-60Hz
- ∴ Power: 8W; 12W; 20W; 24W
- ∴ Driver: non-isolated driver
- ∴ Colour temperature: 3000K; 4000K
- ∴ Colour body: White
- ∴ Material: Aluminium
- ∴ Beam angle: 24°
- ∴ CRI: Ra≥80
- ∴ Power factor: 0.5
- ∴ Protection level against moisture and dust: IP44



FEATURES »

- ∴ Energy-saving fixture in replacement of fluorescent downlights
- ∴ Safety, low voltage operation
- ∴ Installation in suspended ceilings
- ∴ Pleasant and uniform light distribution
- ∴ Low power consumption
- ∴ Instant light with maximum luminous flux
- ∴ Environmentally friendly - no mercury and lead
- ∴ No ultraviolet and infrared rays
- ∴ Resistant to shock and vibration-free body
- ∴ Modern luminaire designed for hotels, offices, conference halls, museums and restaurants.
- ∴ High degree of protection
- ∴ Lightweight construction

TECHNICAL SPECIFICATION SHEET

PRODUCT DETAILS »

Catalogue number	Watt (W)	Whole fixture lumens (lm)	Colour temp. (K)	Size (mm)	Cut hole (mm)	Colour body	WITH THE POSSIBILITY OF EMERGENCY DRIVER
92DLTS0840/WH	8	560	4000	85x50	75	white	Yes
92DLTS0830/WH	8	560	3000	85x50	75	white	Yes
92DLTS1240/WH	12	840	4000	110x60	90	white	Yes
92DLTS1230/WH	12	840	3000	110x60	90	white	Yes
92DLTS2040/WH	20	1400	4000	135x70	120	white	Yes
92DLTS2030/WH	20	1400	3000	135x70	120	white	Yes
92DLTS2440/WH	24	1680	4000	160x80	145	white	Yes
92DLTS2430/WH	24	1680	3000	160x80	145	white	Yes

DIMENSION »

Catalog number	Depth(mm)	Height(mm)
92DLTS0840/WH	85	85
92DLTS0830/WH	85	85
92DLTS1240/WH	110	110
92DLTS1230/WH	110	110
92DLTS2040/WH	135	135
92DLTS2030/WH	135	135
92DLTS2440/WH	160	160
92DLTS2430/WH	160	160

