


LAMP PHOTOMETRIC REPORT

MODEL: 93PFLD6030/BL		
POWER: 60W	VOLTAGE: 230V	WORKING VOLTAGE: 230V
MANUFACTURER: Elmark Industries JSC		

TOTAL FLUX: 5175.6 lm



γ	C0	C45	C90	C135	C180	C225	C270	C315	γ	Φ zone	Φ total	%
10	5991	5445	4902	5504	5997	5259	4591	5206	0- 10	533.0	533.0	10.3
20	5478	4406	3422	4464	5497	4202	3289	4153	10- 20	1369	1902	36.8
30	3578	3221	2198	3228	3644	3070	1804	3012	20- 30	1705	3607	69.7
40	1195	1306	235.8	1330	1258	1092	196.7	1089	30- 40	1149	4756	91.9
50	240.0	140.9	65.35	143.9	241.6	120.8	54.92	113.1	40- 50	329.5	5085	98.3
60	53.10	31.17	23.47	31.12	51.27	26.87	19.85	26.42	50- 60	70.65	5156	99.6
70	7.641	6.621	5.501	6.669	7.320	4.710	2.039	4.633	60- 70	17.72	5174	100
80	0.4556	0.3772	0.2724	0.3856	0.3556	0.3094	0.3217	0.3036	70- 80	1.639	5175	100
90	0.2802	0.2239	0.1908	0.2133	0.3664	0.3230	0.2835	0.3186	80- 90	0.3136	5176	100
100									90-100			
110									100-110			
120									110-120			
130									120-130			
140									130-140			
150									140-150			
160									150-160			
170									160-170			
180									170-180			
DEG	LUMINOUS INTENSITY:cd									UNIT:lm		

C Range: 0 - 360DEG
C Interval: 10.0DEG
Test Speed: HIGH
Temperature:25.3°C
Operators:
Test Date:31 August 2022

γ Range: 0 - 90DEG
 γ Interval: 2.5DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.00.456
Humidity:65.0%
Test Distance:6.265m [K=1.0000]
Remarks:

```

γ Range: 0 - 90DEG
γ Interval: 2.5DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.00.456
Humidity:65.0%
Test Distance:6.265m [K=1.0000]
Remarks:

```

```

γ Range: 0 - 90DEG
γ Interval: 2.5DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.00.456
Humidity:65.0%
Test Distance:6.265m [K=1.0000]
Remarks:

```