


LAMP PHOTOMETRIC REPORT

MODEL: 95Livia90/BL		
POWER: 6W	VOLTAGE: 230V	WORKING VOLTAGE: 230V
MANUFACTURER: Elmark Industries JSC		

TOTAL FLUX: 424.77 lm



γ	C0	C45	C90	C135	C180	C225	C270	C315	γ	Φ zone	Φ total	%
10	358.8	354.7	348.1	347.7	354.8	356.6	359.3	361.7	0- 10	36.09	36.09	8.5
20	261.9	258.4	252.7	254.3	264.2	261.3	263.7	264.8	10- 20	86.09	122.2	28.8
30	172.0	169.4	166.4	170.3	175.3	169.0	173.9	173.1	20- 30	97.87	220.0	51.8
40	104.3	104.8	101.4	104.5	107.4	103.0	104.4	103.3	30- 40	84.51	304.6	71.7
50	59.55	60.37	56.47	58.05	60.26	58.15	56.43	56.37	40- 50	61.13	365.7	86.1
60	29.93	30.94	28.42	28.55	29.60	28.27	26.18	26.71	50- 60	37.79	403.5	95
70	9.328	10.74	9.803	9.092	9.210	7.825	6.336	6.819	60- 70	17.67	421.1	99.1
80	0.4354	0.5925	0.5601	0.5205	0.4364	0.2900	0.2027	0.2334	70- 80	3.534	424.7	100
90	0.0450	0.0458	0.0410	0.0387	0.0317	0.0310	0.0273	0.0248	80- 90	0.0915	424.8	100
100									90-100			
110									100-110			
120									110-120			
130									120-130			
140									130-140			
150									140-150			
160									150-160			
170									160-170			
180									170-180			
DEG	LUMINOUS INTENSITY:cd									UNIT:lm		

C Range: 0 - 360DEG
C Interval: 10.0DEG
Test Speed: MEDIUM
Temperature:25.3°C
Operators:
Test Date:19 December 2022

γ Range: 0 - 90DEG
 γ Interval: 2.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.00.456
Humidity:65.0%
Test Distance:6.265m [K=1.0000]
Remarks:

```

γ Range: 0 - 90DEG
γ Interval: 2.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.00.456
Humidity:65.0%
Test Distance:6.265m [K=1.0000]
Remarks:

```

