


LAMP PHOTOMETRIC REPORT

MODEL: 99POM1505030/WH		
POWER: 50W	VOLTAGE: 230V	WORKING VOLTAGE: 230V
MANUFACTURER: Elmark Industries JSC		

TOTAL FLUX: 4946.7 lm



γ	C0	C45	C90	C135	C180	C225	C270	C315	γ	Φ zone	Φ total	%
10	1855	1862	1859	1843	1840	1844	1858	1864	0- 10	179.0	179.0	3.62
20	1722	1745	1750	1710	1697	1711	1746	1748	10- 20	507.6	686.5	13.9
30	1514	1556	1573	1508	1479	1510	1569	1560	20- 30	754.5	1441	29.1
40	1252	1313	1344	1256	1212	1259	1340	1319	30- 40	884.7	2326	47
50	969.8	1034	1079	974.5	927.5	977.5	1075	1040	40- 50	887.5	3213	65
60	685.7	743.5	791.4	684.0	640.2	688.2	789.7	750.2	50- 60	774.6	3988	80.6
70	404.1	453.3	498.4	397.3	360.8	401.9	499.4	459.8	60- 70	571.0	4559	92.2
80	146.9	183.2	221.3	134.9	110.5	139.5	222.9	189.0	70- 80	314.2	4873	98.5
90	4.811	5.684	3.344	2.819	2.049	2.476	3.015	6.090	80- 90	73.64	4947	100
100									90-100			
110									100-110			
120									110-120			
130									120-130			
140									130-140			
150									140-150			
160									150-160			
170									160-170			
180									170-180			
DEG	LUMINOUS INTENSITY:cd									UNIT:lm		

C Range: 0 - 360DEG
C Interval: 10.0DEG
Test Speed: HIGH
Temperature:25.3°C
Operators:
Test Date:01 December 2022

γ Range: 0 - 90DEG
 γ Interval: 2.5DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.00.456
Humidity:65.0%
Test Distance:6.265m [K=1.0000]
Remarks:

```

γ Range: 0 - 90DEG
γ Interval: 2.5DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.00.456
Humidity:65.0%
Test Distance:6.265m [K=1.0000]
Remarks:

```

```

γ Range: 0 - 90DEG
γ Interval: 2.5DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.00.456
Humidity:65.0%
Test Distance:6.265m [K=1.0000]
Remarks:

```